

LUNATAK NW 1192 F ZP

High performance hot melt adhesive for the construction of diaper hook and loop fastening and elastic diaper ear applications. Excellent shear adhesion to hook material, stretchable composites and nonwoven webs.

Raw Materials Base	: Synthetic polymer
Appearance	: Pale yellow
Ring & Ball Softening Point	: 94°C
Viscosity@175°C	: ca. 7300 cPs
Application Temperature	: 140 - 180°C
Application Method	: Slot coat, fine line or non-contact coat
Packaged Size	: 15 kg carton
Storage Life	: 12 months minimum in unopened pack and protected from sun, dust moisture and high temperatures.
Cleaning	: Consult equipment manufacturer for clean-up procedures. After clean-up, flush the applicator thoroughly with hot melt to purge the system.
Health and Safety	: To minimise the risk of burns, the use of eye protection and protective clothing is recommended when working near a hot melt applicator. To minimise the risk of flammable vapours, do not exceed a melt temperature of 200°C. Prevent the build-up of vapours. Extinguish all sources of ignition during hot melt use. For further information see Material Safety Data Sheet or label.

Caution

Since the required ultimate performance, the substrates used and the production techniques differ, it is essential that this product is fully evaluated under both end use and production conditions before commercial production is embarked upon. Ageing characteristics of the bond should also be considered. If changes in substrates or production conditions occur re-evaluation may be required.