SAFETY DATA SHEET

Version	Revision Date:	SDS Number:	Date of last issue: -
1.0	07.08.2020	100000012838	Date of first issue: 07.08.2020

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : FULLATAK SC1000 NAT
Product code : 100000012838

Manufacturer or supplier's details

Company : H.B. Fuller Company Australia Pty. Ltd.

Address : 16-22 Red Gum Drive Dandenong South, VIC 3175

Telephone : +611800423855

Emergency telephone number : 18000 74234 (AU) 0800 446 881 (NZ)

Recommended use of the chemical and restrictions on use

Recommended use : Solvent based adhesive

Restrictions on use : For industrial use only.

SECTION 2. HAZARDS IDENTIFICATION

GHS Classification

Flammable liquids	:	Category 2
Skin corrosion/irritation	:	Category 2
Serious eye damage/eye irritation	:	Category 2A
Skin sensitisation	:	Category 1
Germ cell mutagenicity	:	Category 1B
Carcinogenicity	:	Category 1B
Reproductive toxicity	:	Category 2
Specific target organ toxicity - single exposure	:	Category 3 (Respiratory system, Central nervous system)
Specific target organ toxicity - repeated exposure	:	Category 2

Aspiration hazard : Category 1

GHS label elements

Hazard pictograms :

Signal word : Danger

Hazard statements : H225 Highly flammable liquid and vapour.
H304 May be fatal if swallowed and enters airways.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H335 May cause respiratory irritation.
H336 May cause drowsiness or dizziness.
H340 May cause genetic defects.
H350 May cause cancer.
H361 Suspected of damaging fertility or the unborn child.
H373 May cause damage to organs through prolonged or repeated exposure.

Precautionary statements :

Prevention:

P201 Obtain special instructions before use.
P202 Do not handle until all safety precautions have been read and understood.
P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
P233 Keep container tightly closed.
P240 Ground/bond container and receiving equipment.
P241 Use explosion-proof electrical/ ventilating/ lighting equipment.
P242 Use only non-sparking tools.
P243 Take precautionary measures against static discharge.
P260 Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.
P264 Wash skin thoroughly after handling.
P271 Use only outdoors or in a well-ventilated area.
P272 Contaminated work clothing should not be allowed out of the workplace.
P280 Wear protective gloves/ eye protection/ face protection.
P281 Use personal protective equipment as required.

Response:

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/ physician.
P303 + P361 + P353 IF ON SKIN (or hair): Remove/ Take off

immediately all contaminated clothing. Rinse skin with water/ shower.
P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P308 + P313 IF exposed or concerned: Get medical advice/ attention.
P331 Do NOT induce vomiting.
P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
P337 + P313 If eye irritation persists: Get medical advice/ attention.
P362 Take off contaminated clothing and wash before reuse.
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam for extinction.

Storage:

P403 + P233 Store in a well-ventilated place. Keep container tightly closed.
P403 + P235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

None known.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

Chemical name	CAS-No.	Concentration (% w/w)
Solvent naphtha (petroleum), light aliph.	64742-89-8	>= 10 -< 30
Naphtha (petroleum), hydrotreated light	64742-49-0	>= 20 -< 30
toluene	108-88-3	>= 20 -< 30
acetone	67-64-1	>= 20 -< 30
2-methylpentane	107-83-5	>= 10 -< 20
Naphtha (petroleum), hydrotreated light (Contains less than 0.1 % w/w benzene)	64742-49-0	>= 10 -< 30
3-methylpentane	96-14-0	>= 10 -< 20
n-hexane	110-54-3	>= 3 -< 10
Formaldehyde, reaction products with bu-	91673-30-2	>= 1 -< 10

tylphenol		
2,3-dimethylbutane	79-29-8	< 10
Rosin	8050-09-7	< 1

SECTION 4. FIRST AID MEASURES

General advice	:	Show this safety data sheet to the doctor in attendance.
If inhaled	:	Move to fresh air. If symptoms persist, call a physician.
In case of skin contact	:	Wash off with soap and water. Get medical attention if irritation develops and persists.
In case of eye contact	:	Flush eyes with water at least 15 minutes. Get medical attention if eye irritation develops or persists.
If swallowed	:	Do NOT induce vomiting. If victim is fully conscious, give a cupful of water. Never give anything by mouth to an unconscious person. Obtain medical attention.
Most important symptoms and effects, both acute and delayed	:	None known.

SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	:	Use water spray, alcohol-resistant foam, dry chemical or carbon dioxide.
Specific hazards during firefighting	:	Cool closed containers exposed to fire with water spray.
Special protective equipment for firefighters	:	In the event of fire, wear self-contained breathing apparatus. Use personal protective equipment.
Hazchem Code	:	•3YE

SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures	:	Remove all sources of ignition. Beware of vapours accumulating to form explosive concentrations. Vapours can accumulate in low areas. Refer to protective measures listed in sections 7 and 8.
Environmental precautions	:	Prevent spreading over a wide area (e.g. by containment or oil

barriers).

Methods and materials for containment and cleaning up	:	Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal. Non-sparking tools should be used.

SECTION 7. HANDLING AND STORAGE

Local/Total ventilation	:	Use only with adequate ventilation.
Advice on protection against fire and explosion	:	Keep away from open flames, hot surfaces and sources of ignition. Mixture may charge electrostatically: always use earthing leads when transferring from one container to another. Keep in a bunded area. Keep away from sources of ignition - No smoking. Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Use only in area provided with appropriate exhaust ventilation. Vapours may form explosive mixtures with air.
Advice on safe handling	:	Avoid inhalation of vapour or mist. Do not use in areas without adequate ventilation. Keep away from fire, sparks and heated surfaces. Keep container closed when not in use. Take precautionary measures against static discharges.
Hygiene measures	:	Avoid contact with skin, eyes and clothing. Provide adequate ventilation.
Conditions for safe storage	:	Take measures to prevent the build up of electrostatic charge. Use explosion-proof equipment. Keep containers tightly closed in a dry, cool and well-ventilated place. Keep away from sources of ignition - No smoking. Solvent vapours are heavier than air and may spread along floors.
Materials to avoid	:	Strong oxidizing agents
Further information on storage stability	:	Stable under normal conditions.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

Components	CAS-No.	Value type	Control parame-	Basis

		(Form of exposure)	ters / Permissible concentration	
Solvent naphtha (petroleum), light aliph.	64742-89-8	TWA	900 mg/m3	AU OEL
Naphtha (petroleum), hydrotreated light	64742-49-0	TWA	900 mg/m3	AU OEL
toluene	108-88-3	TWA	50 ppm 191 mg/m3	AU OEL
	Further information: Skin absorption			
		STEL	150 ppm 574 mg/m3	AU OEL
	Further information: Skin absorption			
		TWA	20 ppm	ACGIH
acetone	67-64-1	TWA	500 ppm 1,185 mg/m3	AU OEL
		STEL	1,000 ppm 2,375 mg/m3	AU OEL
		TWA	250 ppm	ACGIH
		STEL	500 ppm	ACGIH
2-methylpentane	107-83-5	TWA	500 ppm 1,760 mg/m3	AU OEL
		STEL	1,000 ppm 3,500 mg/m3	AU OEL
		TWA	500 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
Naphtha (petroleum), hydrotreated light (Contains less than 0.1 % w/w benzene)	64742-49-0	TWA	900 mg/m3	AU OEL
3-methylpentane	96-14-0	TWA	500 ppm 1,760 mg/m3	AU OEL
		STEL	1,000 ppm 3,500 mg/m3	AU OEL
		TWA	500 ppm	ACGIH
		STEL	1,000 ppm	ACGIH
n-hexane	110-54-3	TWA	20 ppm 72 mg/m3	AU OEL
		TWA	50 ppm	ACGIH
2,3-dimethylbutane	79-29-8	TWA	500 ppm 1,760 mg/m3	AU OEL
		STEL	1,000 ppm 3,500 mg/m3	AU OEL
		TWA	500 ppm	ACGIH
		STEL	1,000 ppm	ACGIH

Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sam-pling time	Permissible concentra-tion	Basis

toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI
acetone	67-64-1	Acetone	Urine	End of shift (As soon as possible after exposure ceases)	25 mg/l	ACGIH BEI
n-hexane	110-54-3	2,5-Hexanedi-one	Urine	End of shift	0.5 mg/l	ACGIH BEI

Engineering measures : Use local exhaust ventilation or other engineering controls to minimize exposures.

Personal protective equipment

Respiratory protection : Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines.

Filter type : Organic vapour type

Hand protection
Material : Nitrile rubber

Eye protection : Safety glasses with side-shields

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : tan

Odour : solvent-like

Odour Threshold	:	No data available
Melting point/freezing point	:	is not determined
Boiling point/boiling range	:	is not determined
Evaporation rate	:	is not determined
Upper explosion limit / Upper flammability limit	:	Upper flammability limit is not determined
Lower explosion limit / Lower flammability limit	:	Lower flammability limit is not determined
Density	:	0.92 g/cm3
Solubility(ies)		
Water solubility	:	is not determined
Partition coefficient: n-octanol/water	:	No data available
Auto-ignition temperature	:	is not determined
Viscosity		
Viscosity, dynamic	:	is not determined
Viscosity, kinematic	:	is not determined

SECTION 10. STABILITY AND REACTIVITY

Chemical stability	:	The product is chemically stable.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur.
Conditions to avoid	:	Heat, flames and sparks.
Hazardous decomposition products	:	Stable under normal conditions.

SECTION 11. TOXICOLOGICAL INFORMATION

Acute toxicity

Components:

Solvent naphtha (petroleum), light aliph.:

Acute oral toxicity : LD50 Oral (Mouse): 5,000 mg/kg

Acute dermal toxicity : LD50 Dermal (Rabbit): 3,000 mg/kg

toluene:

Acute oral toxicity : LD50 Oral (Rat): 5,580 mg/kg

Acute inhalation toxicity : LC50 (Rat): 12.5 mg/l
Exposure time: 4 h

n-hexane:

Acute dermal toxicity : LD50 Dermal (Rabbit): 3,000 mg/kg

Skin corrosion/irritation

Product:

Remarks : No data available

Serious eye damage/eye irritation

Product:

Remarks : No data available

Chronic toxicity

Germ cell mutagenicity

Product:

Genotoxicity in vitro : Remarks: No data available

Carcinogenicity

Product:

Remarks : No data available

STOT - single exposure

Product:

Remarks : No data available

STOT - repeated exposure

Product:

Remarks : No data available

SECTION 12. ECOLOGICAL INFORMATION

Ecotoxicity

Components:

toluene:

Toxicity to fish	:	LC50 (Oncorhynchus mykiss (rainbow trout)): 5.8 mg/l Exposure time: 96 h Test Type: semi-static test
Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 5.46 - 9.83 mg/l Exposure time: 48 h Test Type: static test
Toxicity to algae/aquatic plants	:	EC50 (Pseudokirchneriella subcapitata (microalgae)): 12.5 mg/l Exposure time: 72 h Test Type: static test

Naphtha (petroleum), hydrotreated light (Contains less than 0.1 % w/w benzene):

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia (water flea)): 2.6 mg/l Exposure time: 96 h Test Type: static test

n-hexane:

Toxicity to fish	:	LC50 (Pimephales promelas (fathead minnow)): 2.1 - 2.98 mg/l Exposure time: 96 h Test Type: flow-through test

Rosin:

Toxicity to daphnia and other aquatic invertebrates	:	EC50 (Daphnia magna (Water flea)): 3.8 - 5.4 mg/l Exposure time: 48 h Test Type: static test

Persistence and degradability

No data available

Bioaccumulative potential

No data available

Mobility in soil

No data available

Other adverse effects

No data available

SECTION 13. DISPOSAL CONSIDERATIONS

Disposal methods

Waste from residues : Dispose of as hazardous waste in compliance with local and national regulations.
The hazard and precautionary statements displayed on the label also apply to any residues left in the container.

SECTION 14. TRANSPORT INFORMATION

International Regulations

UNRTDG

UN number	:	UN 1133
Proper shipping name	:	ADHESIVES
Class	:	3
Packing group	:	II
Labels	:	3

IATA-DGR

Not permitted for transport

IMDG-Code

UN number	:	UN 1133
Proper shipping name	:	ADHESIVES
Class	:	3
Packing group	:	II
Labels	:	3
EmS Code	:	F-E, S-D
Marine pollutant	:	no

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations

ADG

UN number	:	UN 1133
Proper shipping name	:	ADHESIVES
Class	:	3
Packing group	:	II
Labels	:	3
Hazchem Code	:	•3YE

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data

Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

Standard for the Uniform Scheduling of Medicines and Poisons : Schedule 7

Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

The components of this product are reported in the following inventories:

TSCA : Product contains substance(s) not listed on TSCA inventory.

DSL : This product contains one or several components that are not on the Canadian DSL nor NDSL.

REACH : Not in compliance with the inventory

AICS : On the inventory, or in compliance with the inventory

NZIoC : Not in compliance with the inventory

ENCS : Not in compliance with the inventory

KECI : Not in compliance with the inventory

PICCS : Not in compliance with the inventory

IECSC : Not in compliance with the inventory

TCSI : Not in compliance with the inventory

SECTION 16. OTHER INFORMATION

Further information

Revision Date	:	07.08.2020
Contact Point	:	Prepared by: Global Regulatory Department - phone: 1-651-236-5842 - email: msds.request@hbfuller.com
Date format	:	dd.mm.yyyy

Full text of other abbreviations

ACGIH	:	USA. ACGIH Threshold Limit Values (TLV)
ACGIH BEI	:	ACGIH - Biological Exposure Indices (BEI)
AU OEL	:	Australia. Workplace Exposure Standards for Airborne Contaminants.
ACGIH / TWA	:	8-hour, time-weighted average
ACGIH / STEL	:	Short-term exposure limit
AU OEL / TWA	:	Exposure standard - time weighted average
AU OEL / STEL	:	Exposure standard - short term exposure limit

AICS - Australian Inventory of Chemical Substances; AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Con-

trol Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

AU / EN