



FULAFOAM CLEANER

Description

Fulafoam Cleaner is a solvent based cleaner for cleaning uncured or fresh polyurethane from applicator guns, tools and other surfaces. Fulafoam Cleaner can be used to clean applicator guns used for Fulafoam PRO Standard, Fulafoam Flexible and maxbond PRO gun-applied foams and adhesives. Fulafoam Cleaner is formulated to be free of ozone depleting propellants.

Benefits

- Does not contain CFC's and H-CFC's
- Rapid cleaning of uncured polyurethane

Uses

- Cleaning of HB Fuller applicator guns
- Clean up of excess foam or foam adhesive from tools and work surfaces, window frames, window sills, doors, door jambs etc

Yield

One can of Fulafoam Cleaner will be sufficient to clean multiple guns. Cleaning of the gun is not required after every can of foam or adhesive is emptied, however, cleaning every 10-20 canisters is recommended, or more often if only intermittent use of the gun is performed. If the gun will be stored without a canister attached then the gun should be cleaned to prevent and residual polyurethane from jamming the application mechanism

Application

IMPORTANT:

Fulafoam Cleaner contains flammable solvents. Do not smoke or work near any sources of ignition such as naked flames or anything that may generate a spark or high temperature. Shake can at least 20 times before each use to ensure that contents are mixed. For hand cleaning of surfaces or tools attach the red nozzle to the can and gently depress the nozzle. For cleaning of a gun applicator attach the canister to the gun by removing the red nozzle and aligning the thread on the canister and gun and turn until locked in position. To clean the gun open the screw valve at the rear of the gun and gently press trigger to release foam. The rate of extrusion can be varied, by turning the screw thread at the rear of the gun. When gun has been cleaned close the valve at the rear of the gun and remove the canister. Re-open the valve and press the trigger to depressurize the gun. Note: a significant amount of residual cleaner will still be contained in the gun before depressurization so ensure gun is pointed away from anyone before pulling the trigger.

Clean Up

Surfaces surrounding the job area should be protected from accidental contact with Fulafoam Cleaner. Clean up dissolved foam with a rag.

Shelf Life

Twelve months unopened from date of manufacture. If open and is attached to gun, will remain useable for up to 6 weeks.

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia
Tel: +61 1800 423 855
customer.service@hbfuller.com
China & Hong Kong
Tel: +86 20 82068291
cs.china@hbfuller.com
Indonesia
Tel: +62-21-5307232/33

Korea
Tel: +82 2 786 8296
cskorea@hbfuller.com
Malaysia
Tel: +603 3345 5200
New Zealand
Tel: +64 800 555 072
customer.service@hbfuller.com

Philippines
Tel: +63 2 5194073
Taiwan
Tel: +886 2 26033385
Thailand
Tel: +66 2 3757442
Vietnam
Tel: +84 8 22225588





Limitations

- Fulafoam Cleaner foam cannot dissolve cured foam

Safety Information

A Material Safety Data Sheet is available from the H.B. Fuller representative your state, HB Fuller Australia customer service, or downloadable from the HB Fuller web site, www.hbfuller.com.au

Disclaimer

This technical data sheet summarises at the date of issue to the best technical knowledge of HB Fuller Australia. Since HB Fuller Australia cannot anticipate or control the conditions under which the product may be used, each user must, prior to usage, review this technical data sheet in the context of how the user intends to handle and use the product in the workplace. If clarification or further information is needed to ensure that an appropriate assessment can be made, the user should contact this company. Our responsibility for the products sold is subject to our standard terms and conditions, a copy of which is sent to our customers and is also available on request

Version 1
TDS Date: 15/02/2017

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia
Tel: +61 1800 423 855
customer.service@hbfuller.com
China & Hong Kong
Tel: +86 20 82068291
cs.china@hbfuller.com
Indonesia
Tel: +62-21-5307232/33

Korea
Tel: +82 2 786 8296
cskorea@hbfuller.com
Malaysia
Tel: +603 3345 5200
New Zealand
Tel: +64 800 555 072
customer.service@hbfuller.com

Philippines
Tel: +63 2 5194073
Taiwan
Tel: +886 2 26033385
Thailand
Tel: +66 2 3757442
Vietnam
Tel: +84 8 22225588

