



TECHNICAL DATA SHEET

Version 1
09/04/2015

ADVANTRA PHC 9255 A

Type of Adhesive Advantra PHC 9255A is a very light coloured and extremely low odour hot melt adhesive that has excellent high and low temperature properties.

Product Benefits The adhesive has excellent heat stability virtually eliminating char formation and has very good machining properties, with minimal stringing and tailing. This product is designed specifically for applications where a long open time is required. It is worth noting that, although PHC 9255A will not char, any foreign matter introduced into the pot, such as cardboard fibres or dust, could char. To obtain the best performance from this product good housekeeping practices are essential.

Typical Applications

Typical Properties

Raw Material Base	Synthetic polymer & resin
Colour	White
Ring & Ball Softening Point	circa 87 - 89°C
Viscosity at 177 °C (Brookfield)	650 - 830 cP
Application Temperature Range	160 – 190°C
Suggested Application Temperature	170 – 175°C
Application Method	Nozzle, wheel, reservoir pump etc.
Storage Life	1 Year Minimum
Safety Advice	Please refer to the MSDS for safety advice

Made in Australia

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia
Tel: +61 1800 423 855
customer.service@hbfuller.com
China & Hong Kong
Tel: +86 20 82068291
cs.china@hbfuller.com
Indonesia
Tel: +62-21-5307232/33

Korea
Tel: +82 2 786 8296
cskorea@hbfuller.com
Malaysia
Tel: +603 3345 5200
New Zealand
Tel: +64 800 555 072
customer.service@hbfuller.com

Philippines
Tel: +63 2 5194073
Taiwan
Tel: +886 2 26033385
Thailand
Tel: +66 2 3757442
Vietnam
Tel: +84 8 2225588

