



TECHNICAL DATA SHEET

Version 2
19/07/17

FULLATAK SG226

Type of Adhesive FULLATAK SG226 is a solvent based adhesive specifically formulated for bonding synthetic turf and needle punch carpets to most common interior and exterior sub-floors. It may also be used for sporting field installations with approved joining tapes. This product is not recommended for urethane or EVA backed carpets.

Product Benefits
Aggressive tack
High bond strength
Excellent water resistance
Excellent heat resistance
Coverage: 2-3m²/lt

Typical Application INDOOR/OUTDOOR SYNTHETIC TURF ADHESIVE

Typical Properties

Raw material base	Solvent
Appearance	Green
Viscosity (Brookfield)	40,000 – 50,000 cps
Surface Preparation	All subfloor surfaces shall be dry, smooth, sound and clean, free of wax, grease, oil, old adhesive, paint, curing compounds, laitance, bond breakers and all other contaminants that inhibit adequate adhesion to the sub-floor. The sub-floor must also be free from hydrostatic pressure or capillary action. The adhesive should not be used in excessive cold or hot conditions i.e. below 8°C or above 28°C. Uneven or damaged floors should be repaired with a cementitious levelling compound. All subfloors should be tested for moisture content prior to surface priming or application of this adhesive. The moisture content of the sub-floor should not exceed 5.5% and or the relative humidity should not exceed 70%. Do not use this adhesive if the moisture content /relative humidity levels are above the acceptable standards. All subfloors should in accordance with current Australian standard installation practices..

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the H.B. Fuller General Terms and Conditions of Sale applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia
Tel: +61 1800 423 855
customer.service@hbfuller.com
China & Hong Kong
Tel: +86 20 82068291
cs.china@hbfuller.com
Indonesia
Tel: +62-21-5307232/33

Korea
Tel: +82 2 786 8296
cskorea@hbfuller.com
Malaysia
Tel: +603 3345 5200
New Zealand
Tel: +64 800 555 072
customer.service@hbfuller.com

Philippines
Tel: +63 2 5194073
Taiwan
Tel: +886 2 26033385
Thailand
Tel: +66 2 3757442
Vietnam
Tel: +84 8 2225588





TECHNICAL DATA SHEET

Application Information	Stir the adhesive thoroughly before use. For synthetic grass applications, apply the adhesive with a V5 trowel and for needle punched carpet installations apply the adhesive with a V3 trowel. Install the floor-covering into adhesive whilst the adhesive is still wet. As work proceeds, remove any excess adhesive off pile surface or surrounds. As the adhesive is solvent based, when laying outside make sure that the weather conditions are conducive to laying, as the adhesive takes 4 hours to cure, before being water resistant, and 48 hours before being water proof. It is advisable to use plastic or polythene sheeting to cover work areas if weather becomes unsettled. Roll the floor-covering per the manufacturer's instructions
Limitations	This product is flammable. Use only in well ventilated areas. Keep away from heat, sparks and naked flames. Avoid contact with skin and eyes. Avoid breathing vapours, if swallowed do not induce vomiting, give plenty of water or milk and contact a doctor.
Storage	Do not allow adhesive to freeze, unaffected by freezing when dry.
Shelf life	This adhesive has a shelf life of 12 months from date of manufacture, providing the pail is unopened and under cover at 20°C.
Clean-up	Clean up surfaces and equipment whilst adhesive is still wet using FULLATAK SC Cleaner.
Safety Advice	Please refer to the SDS for safety advice.

Made in Australia

Our Focus is Clear. Perfecting Adhesives.

IMPORTANT: Information, specifications, procedures and recommendations provided ("information") are based on our experience and we believe this to be accurate. No representation, guarantee or warranty is made as to the accuracy or completeness of the information or that use of the product will avoid losses or damages or give desired results. It is purchaser's sole responsibility to test and determine the suitability of any product for the intended use. Tests should be repeated if materials or conditions change in any way. No employee, distributor or agent has any right to change these facts and offer a guarantee of performance.

NOTE TO USER: by ordering/receiving product you accept the **H.B. Fuller General Terms and Conditions of Sale** applicable in the region. Please request a copy if you have not received these. These Terms and Conditions contain disclaimers of implied warranties (including but not limited to disclaiming warranties of fitness for a particular purpose) and limits of liability. All other terms are rejected. In any event, the total aggregate liability of H.B. Fuller for any claim or series of related claims however arising, in contract, tort (including negligence), breach of statutory duty, misrepresentation, strict liability or otherwise, is limited to replacement of affected products or refund of the purchase price for affected products. H.B. Fuller shall not be liable for loss of profit, loss of margin, loss of contract, loss of business, loss of goodwill or any indirect or consequential losses arising out of or in connection with product supply.

Nothing in any term shall operate to exclude or limit H.B. Fuller's liability for fraud, gross negligence or for death or personal injury caused by negligence or for breach of any mandatory implied terms.

Australia
 Tel: +61 1800 423 855
 customer.service@hbfuller.com
China & Hong Kong
 Tel: +86 20 82068291
 cs.china@hbfuller.com
Indonesia
 Tel: +62-21-5307232/33

Korea
 Tel: +82 2 786 8296
 cskorea@hbfuller.com
Malaysia
 Tel: +603 3345 5200
New Zealand
 Tel: +64 800 555 072
 customer.service@hbfuller.com

Philippines
 Tel: +63 2 5194073
Taiwan
 Tel: +886 2 26033385
Thailand
 Tel: +66 2 3757442
Vietnam
 Tel: +84 8 2225588

